



# DURA

LAMP



## DURABLE PENDANT



## PENDANT

## TRACK

PLUS

SIZE:  
Ø 6 CM 15 CM AND 30 CM

WARRANTY:  
3 YEARS\*

- 1 TYPE**  
Pendant luminaire for direct lighting, for replaceable lamp with GU10 socket.
- 2 CHARACTERISTICS**  
Minimal, simple design and precise finishing. Available in different size and colours. Track version for use on Eurostandard rails and various brands of rails: Staff, Nordlux, Nordic, Global, etc.
- 3 OPTIC**  
Can be used with all GU10 lamps in the catalogue: select the desired power and beam opening.
- 4 MATERIAL**  
Die-cast painted aluminium body.

**5** NB  
Cable length 1,5 m.

## DURABLE TRACK SPOT

PLUS

SIZE:  
Ø 6 CM 13 CM

WARRANTY:  
3 YEARS\*

- 1 TYPE**  
Professional LED projectors for track mounting with GU10 lampholder.
- 2 CHARACTERISTICS**  
Can be used with Eurostandard Plus tracks as well as with other brands: Staff, Nordlux, Nordic, Global, etc.
- 3 OPTIC**  
Can be used with all GU10 lamps in the catalogue: select the desired power and beam opening.
- 4 MATERIALS**  
Die-cast painted aluminium body.



**DURA**  
LAMP

## DURABLE APPLIQUE IP44



PLUS

SIZE:  
6,7 CM 15,2 CM

WARRANTY:  
3 YEARS\*

1

### TYPE

Double emission wall light for replaceable lamp with GU10 socket.

2

### CHARACTERISTICS

The design of the fixture sees the positioning of the lamp a few centimetres from the wall allowing the cone of light to develop on the wall in a harmonious way, without excessive glare.

3

### OPTICS

Can be used with all GU10 lamps in the catalogue: select the desired power and beam opening.

4

### MATERIALS

Aluminium body with epoxy coating; glass diffusers.

5

### MONTING

By means of the rear bracket.

## INGROUND WALK-ON IP67

PLUS

SIZE:  
Ø 11 CM 12,5 CM

WARRANTY:  
3 YEARS\*

1

### TYPE

Walk-on fixture for inground installation complete with GU10 lampholder.

2

### CHARACTERISTICS

Complete with steel outer ring and screws, clear glass.

3

### OPTIC

Can be used with all GU10 lamps in the catalogue: select the desired power and beam opening.


4

### MATERIALS

Metal body, brushed steel ring, shockproof IK10 glass screen; plastic sleeve.




PLUS	220-240V 50/60Hz	IP20	-25° +35°C		G3
------	---------------------	------	---------------	--	----




art.		Ø	L	L1			
DBTR160-W		60	130	170	290	980535	20
DBTR160-B		60	130	170	290	981082	20

PLUS	220-240V 50/60Hz	IP20	-25° +35°C		G3
------	---------------------	------	---------------	--	----




art.		Ø	L				
DBSP115-W		60	150			980573	20
DBSP115-B		60	150			981105	20
DBSP130-W		60	300			980559	20
DBSP130-B		60	300			981099	20




art.		Ø	L				
DBSP215-W		60	150			982225	20
DBSP215-B		60	150			982232	20
DBSP230-W		60	300			982249	20
DBSP230-B		60	300			982256	20



PLUS	220-240V 50/60Hz	IP44	-25° +35°C		G3
------	---------------------	------	---------------	--	----




art.		L	L1	H			
DBAQ100-W		67	95	152	550	980610	20
DBAQ100-B		67	95	152	550	981129	20



art.		L	L1	H			
DBAT100-W		67	93	152	470	980597	20
DBAT100-B		67	93	152	470	981112	20

PLUS		220-240V 50/60Hz	IP67	IK10	-20° +35°C		G3
------	--	---------------------	------	------	---------------	--	----



art.		Ø	H			
DBIN100-0		110	125		980627	20

The luminaire does not include the lamp: choose the most suitable lamp from our range.  
For professional use we suggest items 28530LL/28540LL.